

DECLARATION OF CONFORMITY

26 d. 04 month 2012 year

Authorized representative: JSC "Mida LT",
Gamyklos g. 19, Gargzdai, LT-96155, Lithuania. Phone: Vostochny promuzel, 21, Bld 58
+370 46 45 53 56; fax: +370 46 45 51 67; info@mida.lt;
www.mida.lt

Manufacturer: "TECHNONIKOLCHOVA" LLC
Gamyklos g. 19, Gargzdai, LT-96155, Lithuania. Phone: Vostochny promuzel, 21, Bld 58
390000,Ryazan, Russia
phone (4912) 911-2228, 911-221;
fax (4912) 911-2221; www@shinglas.ru

EN 544:2011

Bitumen shingles for roof covering
Type 4X2

External fire performance: FROOF

Reaction to fire: Class E

Characteristics	Test method according to EN 544:2011 or other standards	Units	Value or statement	Declared tolerances
Mass of bitumen	6.2	g/m ²	1550	± 50
Height (H)	6.2	mm	335	± 3,0
Width (W)	6.3	mm	1000	± 3,0
Tensile properties: maximum tensile force (width) maximum tensile force (height)	EN 12311-1	N/50 mm		
Resistance to tearing (nail shank)	EN 12310-1	N	800 600	± 200 ± 200
Water absorption radiation	6.4.3	%	≤ 1,5	
Blistering	6.4.5		Pass	
Flow resistance at elevated temperature	EN 1110	°C	≤2 mm at 90 °C	
Adhesion of granules and flakes of slate	EN 12039	g	≤ 1,5	
Surface of overlapping of the lower layer by the upper layer in the visible part	6.34	mm	≥ 49	

The Authorized representative JSC "Mida LT", declares under its sole responsibility that the product

TILERCAT QUADRO

Product Passport No.8 (April, 2012)

to which this declaration relates is in conformity with the following standard

EN 544:2011 Bitumen Shingles with mineral and/or synthetic reinforcements

and can be used for installation of the new pitched roofs and reconstruction of the old ones.

Method of application: it fastens mechanically to the smooth and continuous basis of pitched roofs with roofing nails according to the manufacturer installation instruction.

Manufacturer references:

- Do not use this material on pitched roofs the inclination of which is ≤12°.
- Packages with shingles should be stored in horizontal position combined on wooden pallets no more than 12 rows of packages in height and should be protected against moisture, heat (temperature not higher than +40°C) and mechanical damage.
- In the cold season the material should be kept at the temperature not lower than (20±3)°C not less than 24 hours before installation.
- Surrounding temperature during installation should be not less than +6°C.

(Duty, name, surname of an authorized person)* *Minda LT*

(Signature) *Minda LT*

